AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, listings of claims in the application:

Listing of Claims:

Claims 1-30(canceled)

- 31. (currently amended) A process for treating a fabric in need of treatment comprising the steps of:
 - a. exposing a fabric to a lipophilic fluid and water, said lipophilic fluid being selected from the group consisting of linear or cyclic siloxanes, perfluorinated amines. C6 or higher diols, polyol esters, and mixtures thereof;
 - b. recovering said lipophilic fluid and said water in the form of a lipophilic fluid and water emulsion from said fabric;
 - c. exposing said lipophilic fluid and water emulsion to an absorbent matrix comprising an absorbent material comprising a polymer selected from the group consisting of surface cross-linked polyacrylate, surface cross-linked polyacrylamide and mixtures thereof, in order to effect the removal of said water from said lipophilic fluid and water emulsion such that the lipophilic fluid is recovered as collected lipophilic fluid.
- 32. (previously presented) A process according to Claim 31 wherein said absorbent matrix comprises a spacer material in an amount from at least about 1% to at most about 50% by volume of the dry bulk matrix and is selected from the group consisting of sand, silica, aluminosilicates, glass microspheres, clay, layered silicates, wood, natural textile materials, synthetic textile materials, alumina, aluminum oxide, aluminum silicate, zinc oxide, molecular sieves, zeolites, activated carbon, diatomaceous earth, hydrated silica, mica, microcrystalline cellulose, montmorillonite, peach pit powder, pecan shell powder, talc, tin oxide, titanium dioxide, walnut shell powder, particles of different metals or metal alloys and mixtures thereof.
- 33. (previously presented) A process according to Claim 32 wherein said spacer material is selected from the group consisting of particles made from polybutylene, polyethylene, polyisobutylene, polymethylstyrene, polypropylene, polystyrene, polyurethane, nylon, polytetrafluoroethylene and mixtures thereof.

- 34. (previously presented) A process according to Claim 31 wherein said absorbent material comprises a high surface area material in an amount from at least about 1% to at most about 50% by volume of the dry bulk matrix.
- 35. (previously presented) A process according to Claim 31 wherein said absorbent material has a morphology selected from the group consisting of fibrous morphology, particulate morphology and mixtures thereof.
- 36. (previously presented) A process according to Claim 31 wherein said absorbent matrix is in a form selected from the group consisting of a porous woven sheet impregnated with absorbent materials, a film, a membrane and mixtures thereof.
- 37. (previously presented) A process according to Claim 31 further comprising the step of passing said lipophilic fluid and water emulsion through a particulate matter filter such that particles and particle aggregates about 1 micron or larger are removed.
- 38. (previously presented) A process according to Claim 31 further comprising the step of exposing said lipophilic fluid and water emulsion to activated carbon.
- 39. (previously presented) A process according to Claim 31 further comprising the step of triggering said absorbent material to release said removed water by exposing said absorbent material to a trigger mechanism selected from the group consisting of light, pH, temperature, sound, electric field, pressure, ionic strength, vibration and mixtures thereof.
- 40. (previously presented) A process according to Claim 31 wherein the temperature of said lipophilic fluid and water emulsion is at least about 10°C and at most about 50°C prior to exposing said emulsion to said absorbent material.
- 41. (previously presented) A process according to Claim 31 further comprising the step of exposing said collected lipophilic fluid to activated carbon.
- 42. (previously presented) A process according to Claim 31 further comprising the step of exposing said removed water to activated carbon.
- 43. (previously presented) A process according to Claim 31 wherein said lipophilic fluid and water emulsion comprises up to about 10% emulsifier by weight of the emulsion.

- 44. (previously presented) A process according to Claim 31 wherein said lipophilic fluid comprises alinear siloxan and/or a cyclic siloxane.
- 45. (previously presented) A process according to Claim 31 wherein said lipophilic fluid comprises decamethylcyclopentasiloxane.
- 46. (previously presented) A process according to Claim 31 wherein said lipophilic fluid and water emulsion also comprises adjunct ingredients selected from the group consisting of enzymes, bleaches, surfactants, fabric softeners, perfumes, antibacterial agents, antistatic agents, brighteners, dye fixatives, dye abrasion inhibitors, anti-crocking agents, wrinkle reduction agents, wrinkle resistance agents, soil release polymers, sunscreen agents, anti-fade agents, builders, sudsing agents, composition malodor control agents, composition coloring agents, pH buffers, waterproofing agents, soil repellency agents and mixtures thereof.
- 47. (currently amended) A system for removing water from a lipophilic fluid and water emulsion removed from a fabric exposed to a lipophilic fluid and water, said system comprising exposing said emulsion to an absorbent matrix comprising an absorbent material comprising a polymer selected from the group consisting of surface cross-linked polyacrylate, surface cross-linked polyacrylamide and mixtures thereof, in order to effect the removal of said water from said lipophilic fluid and water emulsion such that the lipophilic fluid is recovered as collected lipophilic fluid; and said lipophilic fluid is selected from the group consisting of linear or cyclic siloxanes, perfluorinated amines. C6 or higher diols, polyol esters, and mixtures thereof.
- 48. (previously presented) A system according to Claim 47 wherein said absorbent matrix comprises a spacer material selected from the group consisting of sand, silica, aluminosilicates, glass microspheres, clay, layered silicates, wood, natural textile materials, synthetic textile materials, alumina, aluminum oxide, aluminum silicate, zinc oxide, molecular sieves, zeolites, activated carbon, diatomaceous earth, hydrated silica, mica, microcrystalline cellulose, montmorillonite, peach pit powder, pecan shell powder, talc, tin oxide, titanium dioxide, walnut shell powder, particles of different metals or metal alloys and mixtures thereof.
- 49. (previously presented) A system according to Claim 48 wherein said spacer material is selected from the group consisting of particles made from polybutylene, polyethylene, polyisobutylene, polymethylstyrene, polypropylene, polystyrene, polyurethane, nylon, polytetrafluorethylen and mixtures thereof.

- 50. (previously presented) A system according to Claim 47 further comprising the step of passing said lipophilic fluid and water emulsion through a particulate matter filter such that particles and particle aggregates about 1 micron or larger are removed.
- 51. (previously presented) A system according to Claim 47 wherein said absorbent matrix is in a form selected from the group consisting of a porous woven sheet impregnated with absorbent polymers, a film, a membrane and mixtures thereof.